



5-PIN MALE EURO  
QD CONNECTOR

18.9  
[.74]

17.5-20.3  
[0.69-0.8]

FIRST BEAM

4X M4 X 0.7  
19 in-lbs [1.6 ft-lbs]  
RECOMMENDED TORQUE

42.0  
[1.65]

LAST BEAM

758.68  
[29.869]

32.5  
[1.28]

42.3  
[1.67]

38.0  
[1.5]

6X 4.5  
[.18]

3X 25.0  
[.98]

4X 8.5  
[.33]

PLACE BRACKETS TO ENSURE  
THE UNSUPPORTED LENGTH IS  
LESS THAN 900mm

39.6  
[1.56]

38.2  
[1.5]

48.7  
[1.92]

ISOMETRIC VIEW  
SCALE 3:10

ISOMETRIC VIEW  
SCALE 3:10

68.2  
[2.68]

7.5  
[.3]

(25.0 )  
[.98]

NOTES:  
1. ALL DIMENSIONS ARE MILLIMETERS [INCHES] UNLESS OTHERWISE NOTED.  
2. REFER TO "www.bannerengineering.com" FOR ADDITIONAL DATA AND SPECIFICATIONS.

This drawing is the property  
of BANNER ENGINEERING CORP.  
Any use or reproduction,  
in any form, without prior  
written permission of  
Banner is prohibited.  
© 2015 Banner Engineering Corp.

**BANNER**

BANNER ENGINEERING CORP.  
www.bannerengineering.com

TITLE

S4BR30 SLC 750MM

SIZE

D

DRAWING NO.

228971

REV.

A

SCALE

3:4

SHEET

1

OF 1

CREO