


**LED Dome Light (150 mm)**

**Features**

	<ul style="list-style-type: none"> <li>• Dome lights provide uniform, diffused lighting</li> <li>• Good for applications with reflective and uneven surfaces</li> <li>• Continuous light model available</li> <li>• Black anodized aluminum housing</li> </ul>
---	--

**Models**


Models	Illumination Type	Color	Cable	Supply Voltage	Supply Current	Connections
LEDRD150N*	Continuous diffused light	Red 636 nm	4.5m (15') with flying leads	24V dc ±10% with voltage regulation of ± 1%	80 mA	Blue = +V White = dc common Black = shield

\* This model is not stocked and is non-returnable


**Specifications**

Feature	Description
Useful Life	60,000 hours
Environmental Rating	IEC IP20; NEMA 1
Operating Conditions	Temperature: 0° to 40°C (+32° to 104°F)
	Maximum relative humidity: 95% at 40°C (non-condensing)

## Dimensions



## Accessories - Continuous Power Supplies

Models	Input	Input Cord	Output	Output Cable	Used with	
<b>PSC-24</b>	100-250V ac 60 Hz	North America (NEMA 5 -15)	24V dc $\pm 5\%$ with voltage regulation of $\pm 1\%$ 2.2 A max	1.8 m (6') 2-wire Unterminated	Continuous types: <b>LEDRD150N</b>	
<b>PSC-24E</b>		Cont. Europe (Schuko CEE 7)				