

EZ-SCREEN Single & Multi-Beam:

- 2-beam system: beam spacing 500 mm
 - 3-beam system: beam spacing 400 mm
 - 4-beam system: beam spacing 300 mm
 - Short range from 0,8 m to 20 m
 - Long range from 15 m to 70 m
 - Highly visible status indicators on both the emitter and receiver





Muting Module MM-TA-12B:

- Compact housing IP65, Quick Disconnect I/O ports
- Universal safety stop interface (USSI) for connection of supplemental safeguarding devices
- Easy configuration for: Auto/manual reset, one/two direction muting, 2 or 4 mute devices input, backdoor timer, override, external device monitoring ...

EZ-SCREEN™ 14 mm/30 mm ODC:

- Choose from 20 sizes in 150 mm increments: 14 mm resolution models with defined areas from 150 mm to 1200 mm and 30 mm resolution models with defined areas from 150 mm to 1800 mm
 - Range from 0,1 m to 6 m (14 mm resolution models) and from 0,1 m to 18 m (30 mm resolution models)
 - Reduced resolution setting
 - Visible diagnostic indicators for system condition and operating status
 - Bargraph display

on receiver indicates alignment



Optional Interface Module:

- 24 V dc operation
- Outputs rated at 6 A
- 22,5 mm DIN-rail mountable housing
- 2 models available:

IM-T-11A: 3 safety normally open contacts
IM-T-9A: 2 safety normally open contacts and
1 normally closed non-safety contact

TURCK BANNER Ltd.:

Sensors and equipment for industrial control and automation:

- Inductive, magnet-inductive, photoelectric, ultrasonic, capacitive, pressure and flow sensors
- Ex interfaces
- Bus systems
- Temperature controls
- Cables and cordsets
- Safety systems
- Laser measurement and inspection devices

Turck Banner Ltd.

Blenheim House Hurricane Way, Wickford Essex SS11 8YT

www.turckbanner.co.uk

Phone: +44 (0)1268 578 888 Fax: +44 (0)1268 763 648 info@turckbanner.co.uk



A014 02/04 TB Ltd.