



1 **EU-TYPE EXAMINATION CERTIFICATE**

2 Equipment intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU

3 Certificate Number: **Sira 13ATEX2058X** Issue: **9**

4 Equipment: **Type K30L and K50L LED Indicator Lights**

5 Applicant: **Banner Engineering Corporation**

6 Address: **9714 Tenth Avenue North  
Minneapolis  
Minnesota 55441  
USA**

7 This equipment and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

8 CSA Group Netherlands B.V., notified body number 2813 in accordance with Articles 17 and 21 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in the confidential reports listed in Section 14.2.

9 Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the schedule to this certificate, has been assured by compliance with the following documents:

EN IEC 60079-0:2018 EN 60079-11:2012

10 If the sign 'X' is placed after the certificate number, it indicates that the equipment is subject to Specific Conditions of Use identified in the schedule to this certificate.

11 This EU-Type Examination Certificate relates only to the design and construction of the specified equipment. If applicable, further requirements of this Directive apply to the manufacture and supply of this equipment.

12 The marking of the equipment shall include the following:



II 1 G

II 1 D

I M1

Ex ia IIC T4 Ga

Ex ia IIIC T<sub>200</sub> 130°C Da

Ex ia I Ma

Ta = -40°C to +40°C

(Pi = 3.4W for EPL Ga & Ma and Pi = 2.7W for EPL Da)

Ta = -40°C to +50°C

(Pi = 2.8W for EPL's Ga & Ma and Pi = 2.2W for EPL Da)

Signed: Michelle Halliwell

Title: Director of Operations



Project Number 80074939

This certificate and its schedules may only be reproduced in its entirety and without change  
CSA Group Netherlands B.V. Utrechtseweg 310, Building B42, 6812AR Arnhem, The Netherlands



## SCHEDULE

### EU-TYPE EXAMINATION CERTIFICATE

Sira 13ATEX2058X  
Issue 9

#### 13 DESCRIPTION OF EQUIPMENT

Type K30L and K50L LED Indicator Lights comprise LEDs mounted on a printed circuit board and encapsulated within a plastic housing with a transparent dome. The Type K50L is physically larger than the K30L having more LEDs than the K30L. The indicator lights have either a screw on plug and socket connector or an integral cable fitted for the electrical connections.

The total combined intrinsically safe electrical parameters are:

$U_i = 30\text{ V}$	$I_i = 1\text{ A}$	$P_i$ – Dependent on Equipment Protection Level (EPL) & Ambient
$C_i = 0$	$L_i = 0$	Temperature – See Table Below

$P_i$  Rating:

Equipment Protection Level (EPL)	$P_i$ & associated Ambient Temperature
EPL Ga & Ma	$P_i = 3.4\text{ W @ }40^\circ\text{C ambient temperature}$ $P_i = 2.8\text{ W @ }50^\circ\text{C ambient temperature}$
EPL Da	$P_i = 2.7\text{ W @ }40^\circ\text{C ambient temperature}$ $P_i = 2.2\text{ W @ }50^\circ\text{C ambient temperature}$

The values of  $I_i$  and  $P_i$  are the total of all input current and the total of all input powers at all connections.

**Variation 1** - This variation introduced the following change:

- i. The specification of the material used for the K30 and K50 LED indicator covers was changed, one of the options being removed.

**Variation 2** - This variation introduced the following change:

- i. A number of editorial changes to the documentation.
  - Replace drawing 126905 with drawing 164906.
  - Replace drawing 133593 with drawing 164905.

**Variation 3** - This variation introduced the following change:

- i. The use of an alternative encapsulation material was approved.

**Variation 4** - This variation introduced the following change:

- i. The recognition of minor drawing modifications; these amendments do not affect the aspects of the product that are relevant to explosion safety.
- ii. Compliance with EN 60079-26 is no longer required for Ex ia Ga equipment, therefore this standard has been removed from the certificate.
- iii. Standard EN 60079-0:2012 was updated to EN 60079-0:2012/A11:2013.

**Variation 5** - This variation introduced the following change:

- i. Drawing 173292 has been revised from rev A to rev B to update the cable details for the LED Indicator lights.

Project Number 80074939

This certificate and its schedules may only be reproduced in its entirety and without change  
CSA Group Netherlands B.V. Utrechtseweg 310, Building B42, 6812AR Arnhem, The Netherlands



## SCHEDULE

### EU-TYPE EXAMINATION CERTIFICATE

Sira 13ATEX2058X  
Issue 9

**Variation 6** - This variation introduced the following change:

- i. A number of editorial changes not affecting compliance have been made to drawings for the LED Indicator lights.

**Variation 7** - This variation introduced the following changes:

- i. Following appropriate assessment to demonstrate compliance with the latest technical knowledge, EN 60079-0:2012/A11: 2013 was replaced by EN IEC 60079-0:2018. Where applicable, the markings were updated accordingly to recognise the new standards. As a result of the assessment, reduced P<sub>i</sub> parameters have been derived for the equipment when installed in an explosive dust atmosphere, Equipment Protection Level (EPL) Da. The previous stated P<sub>i</sub> parameters are still applicable for explosive gas and mining atmospheres, EPL's Ga & Ma.
- ii. Drawing/Documentation update

## 14 DESCRIPTIVE DOCUMENTS

### 14.1 Drawings

Refer to Certificate Annexe.

### 14.2 Associated Reports and Certificate History

Issue	Date	Report number	Comment
0	12 July 2013	R26812A/00	The release of the prime certificate.
1	12 February 2014	R26812B/01	Report no. R26812B/00 was replaced by R26812B/01.
2	07 July 2015	R70034003A	The introduction of Variation 1.
3	06 March 2017	R70115581A	This Issue covers the following changes: <ul style="list-style-type: none"><li>• EC Type-Examination Certificate in accordance with 94/9/EC updated to EU Type-Examination Certificate in accordance with Directive 2014/34/EU. (In accordance with Article 41 of Directive 2014/34/EU, EC Type-Examination Certificates referring to 94/9/EC that were in existence prior to the date of application of 2014/34/EU (20 April 2016) may be referenced as if they were issued in accordance with Directive 2014/34/EU. Variations to such EC Type-Examination Certificates may continue to bear the original certificate number issued prior to 20 April 2016.)</li><li>• The introduction of Variation 2.</li></ul>
4	11 July 2017	R70115798A	The introduction of Variation 3.
5	24 April 2018	R70177521A	The introduction of Variation 4.
6	12 September 2018	R70188875A	The introduction of Variation 5.
7	04 February 2019	R70205810A	The introduction of Variation 6. A number of editorial changes not affecting compliance have been made to drawings for the LED Indicator lights.
8	15 October 2019	0344	Transfer of certificate Sira 13ATEX2058X from Sira Certification Service to CSA Group Netherlands B.V.

Project Number 80074939

This certificate and its schedules may only be reproduced in its entirety and without change  
CSA Group Netherlands B.V. Utrechtseweg 310, Building B42, 6812AR Arnhem, The Netherlands



## SCHEDULE

### EU-TYPE EXAMINATION CERTIFICATE

Sira 13ATEX2058X  
Issue 9

Issue	Date	Report number	Comment
9	26 July 2022	R80074932A	The introduction of Variation 7.

#### 15 SPECIFIC CONDITIONS OF USE (denoted by X after the certificate number)

- 15.1 In certain extreme circumstances, the non-metallic enclosure of these LED Indicator Lights could generate an ignition-capable level of electrostatic charge. Therefore, the user/installer shall ensure that the equipment is not installed in a location where it may be subjected to external conditions (such as high-pressure steam) which are conducive to creating a build-up of electrostatic charges on non-conducting surfaces. Additionally, cleaning of the equipment should only be done with a damp cloth. This condition is particularly important if the equipment is used in a zone 0 or zone 20 applications or when installed in dust environments where it is likely to be regularly cleaned.
- 15.2 When more than one intrinsically safe supply (e.g. two or three barriers) is connected to an LED Indicator the combined electrical parameters of the supply must remain intrinsically safe.
- 15.3 The user/installer shall install these LED Indicator Lights taking into account the following ambient temperature ranges:  
 Ta = -40°C to +40°C (Pi = 3.4W for EPL Ga & Ma installations & Pi = 2.7W for EPL Da installations)  
 Ta = -40°C to +50°C (Pi = 2.8W for EPL Ga & Ma installations & Pi = 2.2W for EPL Da installations)

#### 16 ESSENTIAL HEALTH AND SAFETY REQUIREMENTS OF ANNEX II (EHSRs)

The relevant EHSRs that are not addressed by the standards listed in this certificate have been identified and individually assessed in the reports listed in Section 14.2.

#### 17 CONDITIONS OF MANUFACTURE

- 17.1 The use of this certificate is subject to the Regulations Applicable to Holders of CSA Group Netherlands B.V. certificates.
- 17.2 Holders of EU-Type Examination Certificates are required to comply with the conformity to type requirements defined in Article 13 of Directive 2014/34/EU.

Project Number 80074939

This certificate and its schedules may only be reproduced in its entirety and without change  
CSA Group Netherlands B.V. Utrechtseweg 310, Building B42, 6812AR Arnhem, The Netherlands

# Certificate Annexe



Certificate Number: Sira 13ATEX2058X  
Equipment: Type K30L and K50L LED Indicator Lights  
Applicant: Banner Engineering Corporation

## Issue 0

Drawing no.	Sheets	Rev.	Date (Sira stamp)	Title
169013	1 to 8	B	12 Jul 13	DWG K30L IS Final Assembly
169015	1 of 1	B	12 Jul 13	K30L potting procedure
133592	1 of 1	D	12 Jul 13	Base K30 EZ Light
133593	1 of 1	A	12 Jul 13	Cover K30 EZ Light
145878	1 of 1	A	12 Jul 13	Foam spacer EZ Light K30L
133594	1 of 1	A	12 Jul 13	Nut M22 1.5
133595	1 of 1	A	12 Jul 13	Washer assembly
158033	1 of 1	A	12 Jul 13	Schematic diagram K30L EZ light Intrinsically safe
158034	1 to 2	A	12 Jul 13	PCB assy, K30L Intrinsically safe 3 colour
158034	1 of 1	A	12 Jul 13	PCB BOM, Intrinsically safe 3 colour
158032	1 of 1	B	12 Jul 13	PCB RAW, K30L Intrinsic Safe EZ light
119759	1 of 1	-	12 Jul 13	PCB RAW panel (dimensions), T18 EZ light – K30L
158032	1 to 4	B	12 Jul 13	PCB K30L track and component layout
169012	1 to 7	B	12 Jul 13	K50L, IS Final assembly
169014	1 of 1	B	12 Jul 13	K50L, IS potting procedure, QD
168051	1 of 1	B	12 Jul 13	K50L, IS potting procedure, flying lead
162904	1 of 1	C	12 Jul 13	Base K50 IS Black mounting base
126905	1 of 1	E	12 Jul 13	Cover K50 EZ Light
08249	1 of 1	H	12 Jul 13	Nut M30 X 1.5
158252	1 of 1	A	12 Jul 13	Schematic diagram K50L EZ light Intrinsically safe
158358	1 to 2	A	12 Jul 13	PCB assy, K50L Intrinsically safe 3 colour
158358	1 of 1	A	12 Jul 13	PCB BOM, K50L Intrinsically safe 3 colour
158251	1 of 1	B	12 Jul 13	PCB RAW, K50L Intrinsic Safe EZ light
128145	1 of 1	A	12 Jul 13	PCB RAW Panel (dimensions) K50L
158251	1 to 4	B	12 Jul 13	PCB K50L track and component layout
173292	1 of 1	A	21 Jun 13	Flying lead
172442	1 of 1	A	14 Jun 13	K30/K50 IS ATEX/IECEx Markings, Label

## Issue 1

The following drawing was removed:

Drawing No.	Sheets	Rev.	Date (Sira stamp)	Title
172442	1 of 1	A	14 Jun 13	K30/K50 IS ATEX/IECEx Markings, Label

The following drawing was introduced:

Drawing No.	Sheets	Rev.	Date (Sira stamp)	Title
171463	1 of 1	D	12 Feb 14	K30/K50 IS Markings, Label

## Issue 2

Drawing	Sheets	Rev.	Date (Sira stamp)	Title
164905	1 of 1	B	29 Jun 15	Cover K30 IS Light
164906	1 of 1	F	29 Jun 15	Cover K50 IS light

Project Number 80074939

This certificate and its schedules may only be reproduced in its entirety and without change  
CSA Group Netherlands B.V. Utrechtseweg 310, Building B42, 6812AR Arnhem, The Netherlands

# Certificate Annexe



Certificate Number: Sira 13ATEX2058X  
Equipment: Type K30L and K50L LED Indicator Lights  
Applicant: Banner Engineering Corporation

## Issue 3

Drawing	Sheets	Rev.	Date (Sira stamp)	Title
08249	1 of 1	I	09 Feb17	Nut M30 X 1.5
164906	1 of 1	H	09 Feb17	Cover K50 IS EZ Light 2 <sup>nd</sup> GEN
133592	1 and 2	H	09 Feb17	Base K30 EZ Light
164905	1 of 1	C	09 Feb17	Cover K30 EZ Light
133594	1 of 1	B	09 Feb17	Nut M22 1.5
158033	1 of 1	I	09 Feb17	Schematic diagram K30L EZ light Intrinsically safe
158252	1 of 1	F	09 Feb17	Schematic diagram K50L EZ light Intrinsically safe
162904	1 of 1	D	09 Feb17	Base K50 IS Black M30x1.5 mounting base
169015	1 and 2	C	17 Feb 17	K30L Potting Procedure

### Notes

Drawing 126905 has been made obsolete and replaced by drawing 164906.  
Drawing 133593 has been replaced by 164905.  
Refer to section 3 for up issue details of all of the drawings listed above.

## Issue 4

Drawing	Sheets	Rev.	Date (Sira stamp)	Title
168051	1 to 2	C	19 Jun 17	Proc Potting K50L Hazardous Environment Cable Final Assy
169014	1 to 2	C	19 Jun 17	Proc Potting K50L Hazardous Environment QD Final Assy
169015	1 to 2	D	19 Jun 17	Proc Potting K30L Hazardous Environment Final Assy

## Issue 5

Drawing	Sheets	Rev.	Date (Sira stamp)	Title
08249	1 of 1	K	04 Apr 18	Nut M30 X 1.5
133592	1 to 2	I	04 Apr 18	Base K30 EZ Light
133594	1 of 1	C	04 Apr 18	Nut M22 1.5
164906	1 of 1	J	04 Apr 18	Cover K50 IS EZ Light 2 <sup>nd</sup> GEN

## Issue 6

Drawing	Sheets	Rev.	Date (Sira stamp)	Title
173292	1 of 1	B	14 Aug 18	Cable

## Issue 7

Drawing	Sheets	Rev.	Date (Sira stamp)	Title
169015	1 and 2	E	22 Jan 19	Proc potting K30L Hazardous Environment Final assembly
158252	1 of 1	I	22 Jan 19	Schematic diagram K50L EZ light
133592	1 and 2	J	22 Jan 19	Base K30 EZ Light
133594	1 of 1	D	22 Jan 19	Nut M22 X 1.5

Issue 8. No new drawings were introduced

## Issue 9

Drawing	Sheets	Rev.	Date (Stamp)	Title
133592	1 to 2	K	27 Apr 22	Base K30 EZ Light
158033	1 of 1	K	27 Apr 22	Schematic Diagram K30L EZ light Intrinsic Safety
158252	1 of 1	J	27 Apr 22	Schematic Diagram K50L EZ light Intrinsic Safety
168051	1 to 3	D	27 Apr 22	Proc Potting K50L Hazardous Environment Cable Final Assy
169013	1 to 8	C	27 Apr 22	DWG K30L IS Final Assembly

Project Number 80074939

This certificate and its schedules may only be reproduced in its entirety and without change  
CSA Group Netherlands B.V. Utrechtseweg 310, Building B42, 6812AR Arnhem, The Netherlands

# Certificate Annexe



Certificate Number: Sira 13ATEX2058X  
Equipment: Type K30L and K50L LED Indicator Lights  
Applicant: Banner Engineering Corporation

Drawing	Sheets	Rev.	Date (Stamp)	Title
169014	1 to 3	E	27 Apr 22	Proc Potting K50L Hazardous Environment QD Final Assy
171463	1 of 1	E	01 Jun 22	K30/K50 IS Markings Label
173292	1 of 1	C	27 Apr 22	Cable
217424*	1 & 2	L	27 Apr 22	Dwg Hex Nut with Knurl M30 x 1.5

\* Drawing No. 217424 replaces previous Nut Drawing No. 08249 (last Rev K)

Project Number 80074939

This certificate and its schedules may only be reproduced in its entirety and without change  
CSA Group Netherlands B.V. Utrechtseweg 310, Building B42, 6812AR Arnhem, The Netherlands