

## Features

The temperature, humidity, and dew point sensor works in a variety of environments to provide temperature, humidity, and dew point measurements via IO-Link.

- Temperature, humidity, and dew point monitoring in one device
- Rugged over-molded design
- Ships with aluminum grill filter cap
- Optional stainless steel 10 µm sintered filter available separately
- Continuous process data values for temperature, humidity, and dew point
- Ideal for tracking ambient conditions in critical applications
- IO-Link interface for configuration and communication
- Process data profiles available for Smart Sensor and floating point formats for both Fahrenheit and Celsius
- Configurable high and low thresholds for discrete output



## Models

Model Number	Function	Control	Connectors
S15S-TH-KQ	Female connector: Temperature, humidity, and dew point sensor	Male connector: IO-Link	Integral 4-pin M12 male/female quick-disconnect connectors

## IO-Link®

IO-Link® is a point-to-point communication link between a master device and a sensor and/or light. It can be used to automatically parameterize sensors or lights and to transmit process data. For the latest IO-Link protocol and specifications, please visit [www.io-link.com](http://www.io-link.com).

For the latest IODD files, please refer to the Banner Engineering Corp website at: [www.bannerengineering.com](http://www.bannerengineering.com).

## Configuration

The measured sensor values are available via Process Data In.

For more information, see Banner P/N 242289 *S15S IO-Link Temperature, Humidity, and Dew Point Sensor - IO-Link Data Reference Guide* and Banner P/N 242291 *S15S-TH-KQ IO-Link IODD*.

## Wiring Diagrams

Male (IO-Link Master)	Pin	Wire Color	Signal Description
	1	Brown	18 V DC to 30 V DC
	2	White	Discrete (OUT)
	3	Blue	Ground
	4	Black	IO-Link

## Status Indicators

### Power LED Indicator (Green)

- Solid Green = Power On
- Off = Power Off

### IO-Link Communication LED Indicator (Amber)

- Flashing Amber (900 ms On, 100 ms Off) = IO-Link communications are active
- Off = IO-Link communications are not present

### Sensor Value Communication LED Indicator (Amber)

- Solid Amber = Temperature, humidity, and dew point sensor values are between the low threshold and the high threshold.
- Off = Temperature, humidity, or dew point sensor values are less than the low threshold OR greater than the high threshold.
- Default Values for Temperature (Configurable):
  - Low Threshold = 0 °C (32 °F)
  - High Threshold = 49 °C (120 °F)
- Default Values for Humidity (Configurable):
  - Low Threshold = 0%

- High Threshold = 100%
- Default Values for Dew Point (Configurable):
  - Low Threshold = 0 °C (32 °F)
  - High Threshold = 49 °C (120 °F)

## S15S Specifications

### Supply Voltage

18 V DC to 30 V DC at 50 mA maximum

### Power Pass-Through Current

1 A maximum

### Supply Protection Circuitry

Protected against reverse polarity and transient voltages

### Leakage Current Immunity

400 µA

### Resolution

14-bits

### Indicators

Green LED: Power  
 Amber LED 1: IO-Link communications active  
 Amber LED 2: Analog value present

### Connections

Integral 4-pin M12 male/female quick-disconnect connectors

### Construction

Coupling Material: Nickel-plated brass  
 Connector Body: PVC translucent black

### Temperature and/or Humidity Input

Sample Rate: 3 seconds

### Humidity

Measuring Range: 0 to 100% relative humidity (RH)  
 Resolution: 0.1% RH  
 Accuracy:  
 ± 3% at 0 °C to +70 °C (+32 °F to +158 °F) and 10% to 90% RH  
 ± 7% at 0 °C to +70 °C (+32 °F to +158 °F), and 0% to 10% or 90% to 100% RH

### Temperature

Measuring Range: -40 °C to +85 °C (-40 °F to +185 °F)  
 Resolution: 0.1 °C (32.18 °F)  
 Accuracy:  
 -40 °C to 0 °C (-40 °F to +32 °F): ± 0.8 °C (± 1.5 °F)  
 0 °C to +60 °C (+32 °F to +140 °F): ± 0.7 °C (± 1 °F)  
 +60 °C to +85 °C (+140 °F to +185 °F): ± 1.3 °C (± 2.2 °F)

### Operating Conditions

**Temperature:** -40 °C to +70 °C (-40 °F to +158 °F)  
 90% at +70 °C maximum relative humidity (non-condensing)  
**Storage Temperature:** -40 °C to +80 °C (-40 °F to +176 °F)

### Required Overcurrent Protection



**WARNING:** Electrical connections must be made by qualified personnel in accordance with local and national electrical codes and regulations.

Overcurrent protection is required to be provided by end product application per the supplied table.

Overcurrent protection may be provided with external fusing or via Current Limiting, Class 2 Power Supply.

Supply wiring leads < 24 AWG shall not be spliced.

For additional product support, go to [www.bannerengineering.com](http://www.bannerengineering.com).

Supply Wiring (AWG)	Required Overcurrent Protection (A)	Supply Wiring (AWG)	Required Overcurrent Protection (A)
20	5.0	26	1.0
22	3.0	28	0.8
24	1.0	30	0.5

### Certifications



Banner Engineering BV  
 Park Lane, Culliganlaan 2F bus 3  
 1831 Diegem, BELGIUM



Turck Banner LTD Blenheim House  
 Blenheim Court  
 Wickford, Essex SS11 8YT  
 GREAT BRITAIN



### Product Identification



## FCC Part 15 Class B for Unintentional Radiators

(Part 15.105(b)) This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

(Part 15.21) Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.


## Industry Canada ICES-003(B)

This device complies with CAN ICES-3 (B)/NMB-3(B). Operation is subject to the following two conditions: 1) This device may not cause harmful interference; and 2) This device must accept any interference received, including interference that may cause undesired operation.

Cet appareil est conforme à la norme NMB-3(B). Le fonctionnement est soumis aux deux conditions suivantes : (1) ce dispositif ne peut pas occasionner d'interférences, et (2) il doit tolérer toute interférence, y compris celles susceptibles de provoquer un fonctionnement non souhaité du dispositif.

## Dimensions

All measurements are listed in millimeters [inches], unless noted otherwise. The measurements provided are subject to change.




## S15S Accessories


### Temperature-Humidity Filter Caps

<p><b>FTH-FIL-001</b></p> <ul style="list-style-type: none"> <li>Aluminum grill filter cap</li> <li>Factory default, ships with the S15S-TH*Q, M12FT*Q, and Q45 All-in-One sensors</li> </ul>		<p><b>FTH-FIL-002</b></p> <ul style="list-style-type: none"> <li>Stainless steel</li> <li>Sintered to 40-micrometer porosity (for high dust environments.)</li> </ul>	
---	---	---	---

### Cordsets

4-pin A-Code Double-Ended M12 Female to M12 Male Cordsets				
Model	Length	Dimensions (mm)	Pinouts	
BC-M12F4-M12M4-22-1	1 m (3.28 ft)		Female	<p>1 = Brown 2 = White 3 = Blue 4 = Black</p>
BC-M12F4-M12M4-22-2	2 m (6.56 ft)		Male	
BC-M12F4-M12M4-22-5	5 m (16.4 ft)			
BC-M12F4-M12M4-22-8	8 m (26.25 ft)			
BC-M12F4-M12M4-22-10	10 m (30.81 ft)			
BC-M12F4-M12M4-22-15	15 m (49.2 ft)			

4-pin A-Code Double-Ended M12 Female to M12 Male Right-Angle Cordsets				
Model	Length	Dimensions (mm)	Pinouts	
BC-M12F4-M12M4A-22-1	1 m (3.28 ft)		Female	<p>1 = Brown 2 = White 3 = Blue 4 = Black</p>
BC-M12F4-M12M4A-22-2	2 m (6.56 ft)		Male	
BC-M12F4-M12M4A-22-5	5 m (16.4 ft)			
BC-M12F4-M12M4A-22-8	8 m (26.25 ft)			
BC-M12F4-M12M4A-22-10	10 m (30.81 ft)			
BC-M12F4-M12M4A-22-15	15 m (49.2 ft)			

4-pin A-Code Double-Ended M12 Female Right-Angle to M12 Male Right-Angle Cordsets				
Model	Length	Dimensions (mm)	Pinouts	
BC-M12F4A-M12M4A-22-0.3	0.3 m (1 ft)		<p>Female</p> <p>Male</p>	<p>1 = Brown 2 = White 3 = Blue 4 = Black</p>
BC-M12F4A-M12M4A-22-1	1 m (3.28 ft)			
BC-M12F4A-M12M4A-22-2	2 m (6.56 ft)			
BC-M12F4A-M12M4A-22-5	5 m (16.4 ft)			
BC-M12F4A-M12M4A-22-8	8 m (26.25 ft)			
BC-M12F4A-M12M4A-22-10	10 m (30.81 ft)			
BC-M12F4A-M12M4A-22-15	15 m (49.2 ft)			

**Bracket**

<p><b>LMBS15MAG</b></p> <ul style="list-style-type: none"> <li>• Attaches to S15 housing</li> <li>• White polypropylene</li> <li>• 11.8 kg (26 lb) pull force</li> <li>• One piece</li> </ul>	
---	--

## Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

**THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.**

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: [www.bannerengineering.com](http://www.bannerengineering.com).

For patent information, see [www.bannerengineering.com/patents](http://www.bannerengineering.com/patents).