

LQMAC-3xx and LQMAEC-3xxSS Molex Cordsets

Models and Specifications

Molex to Flying Leads or Wall Plug Cordsets				
Model	**Plug Type**	**Countries**	**Length**	**Dimensions**
LQMAC-306	Flying Leads		1.83 m (6 ft)	
LQMAC-306B	NEMA 5-15 grounded (IEC Type B)	United States, Canada, Japan, Puerto Rico, Taiwan		
LQMAC-306D	BS 546 (IEC Type D)	India		
LQMAC-306EF	CEE 7/7 (IEC Type E or F)	Germany, France, South Korea, The Netherlands, Poland, Spain, Turkey		
LQMAC-306G	BS 1363 (IEC Type G)	United Kingdom, Ireland, Singapore, Vietnam		
LQMAC-306I	AS/NZS 3112 (IEC Type I)	China, Australia, New Zealand		
LQMAC-306N	NBR 14136 (IEC Type N)	Brazil		
LQMAC-310B	NEMA 5-15 grounded (IEC Type B)	United States, Canada, Japan, Puerto Rico, Taiwan	3.05 m (10 ft)	
LQMAC-310EF	CEE 7/7 (IEC Type E or F)	Germany, France, South Korea, The Netherlands, Poland, Spain, Turkey		
LQMAC-310G	BS 1363 (IEC Type G)	United Kingdom, Ireland, Singapore, Vietnam		
LQMAC-310I	AS/NZS 3112 (IEC Type I)	China, Australia, New Zealand		
LQMAC-312	Flying Leads		3.7 m (12 ft)	
LQMAC-330	Flying Leads		9.15 m (30 ft)	
LQMAC-330B	NEMA 5-15 grounded (IEC Type B)	United States, Canada, Japan, Puerto Rico, Taiwan		
LQMAC-333	Flying Leads		10.1 m (33 ft)	
LQMAC-350	Flying Leads		15.2 m (50 ft)	

Continuous Run/Cascade Double-Ended Molex Cordsets			
Model	**Length**	**Style**	**Dimensions**
LQMAEC-3005SS	0.15 m (0.49 ft)	Male straight/Male straight	
LQMAEC-301SS	0.305 m (1.00 ft)		
LQMAEC-303SS	0.91 m (2.99 ft)		
LQMAEC-306SS	1.83 m (6.00 ft)		
LQMAEC-312SS	3.66 m (12.01 ft)		
LQMAEC-320SS	6.10 m (20.01 ft)		
LQMAEC-330SS	9.20 m (30.18 ft)		

Current Rating
3 A

Voltage Rating
300 V AC/DC

Minimum Bend Radius
>10× the outside diameter

Outer Diameter
6.8 mm

AWG
18 AWG

Construction
Contact holder: Black nylon
Connector body: Black PVC
Jacket material: Black PVC

Environmental Rating
IP50

Original Instructions
07-Oct-26

© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com

261684
p/n: 261684 Rev. A

Operating Conditions

Operating temperature: –40 °C to +70 °C (–40 °F to +158 °F)

Storage temperature: –40 °C to +70 °C (–40 °F to +158 °F)

90% at +50 °C maximum relative humidity (non-condensing)

Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.

© Banner Engineering Corp. All rights reserved.
www.bannerengineering.com