

# DXMR90 IO-Link Master

 **SNAP SIGNAL**



## 4-Port Programmable IO-Link Master

- Connects IO-Link devices to traditional PLC systems or sends data directly to the cloud
- Saves space and weight compared to traditional block-style form factors
- Rugged IP67/IP68 housing simplifies installation by eliminating the need for a control cabinet
- Communicates over Ethernet/IP, ProfiNet, Modbus TCP, and Modbus RTU

# DXMR90 IO-Link Master



Model	Ethernet Connection	IO-Link Master Connections	Other Connections
DXMR90-4K	One female M12 D-Code Ethernet Connector	Four female M12 connections for IO-Link	One male M12 (Port 0) for incoming power

## Specifications



<b>Power</b>	12 to 30 V DC
<b>Environmental Rating</b>	For Indoor Use Only IP65, IP67, NEMA 1, UL Type 1
<b>Operating Conditions</b>	-40 °C to +70 °C 90% at +70 °C maximum relative humidity (non-condensing)
<b>Storage Temperature</b>	-40 °C to +80 °C
<b>Connections</b>	Five integral 5-pin M12 female quick disconnect One integral 4-pin M12 male quick disconnect One integral 5-pin M12 female D-Code quick disconnect

## Accessories



**SMBR90S**  
Mounting Bracket

### 4-pin M12 D-code to RJ45 Shielded Ethernet\*

**STP-M12D-406**  
1.83 m (6')

**STP-M12D-415**  
4.57 m (15')

**STP-M12D-430**  
9.14 m (30')



### 4-pin Threaded M12 Cordsets Double Ended

**MQDEC-406SS**  
1.83 m (6')

**MQDEC-412SS**  
3.66 m (12')

**MQDEC-430SS**  
9.14 m (30')



### 5-pin Threaded M12 Cordsets Single Ended

**MQDC1-506**  
2 m (6.5')

**MQDC1-515**  
5 m (16.4')

**MQDC1-530**  
9 m (29.5')



\*One 2-meter cordset is included with purchase



Banner Engineering Corp.

9714 10th Avenue North • Minneapolis, MN 55441 • 1-888-373-6767 • www.bannerengineering.com