

GS60 Guide Spotlights



Improve Visibility and Efficiency in Task and Vision Applications

- Reduce errors, improve productivity, and enhance operator interaction with increased visibility provided by the bright, focused spot
- Enhance worker comfort and safety by easily setting lighting levels to match the environment and application needs
- Reliably use in harsh environments with the long-lasting, impact resistant, durable anodized aluminum housing and polycarbonate window

GS60 Guide Spotlights

Color	Control	Models
Daylight White - 5000K	High/low/off	GS60WL4Q
Red		GS60RL4Q
Green		GS60GL4Q
Blue		GS60BL4Q
Yellow		GS60YL4Q
Infrared (IR)		GS60IL4Q
Ultraviolet (UV) - 395 nm		GS60UV395L4Q
Daylight White - 5000K	Adjustable PWM/strobe and 1 to 10 V dimming	GS60WL4AQ
Infrared (IR)		GS60IL4AQ
Ultraviolet (UV) - 395 nm		GS60UV395L4AQ

Specifications



Supply Voltage	12 to 30 V DC
Construction	Housing: Black anodized aluminium Window: Polycarbonate Connector: Nickel-plated M12 quick-disconnect M30 mounting nut: Black anodized aluminium
Operating Conditions	-40 to +50 °C (-40 to +122 °F)
Environmental Rating	IP66, IP67

Accessories



5-Pin M12
Straight connector models listed; for right-angle models, add RA to the end of model number (example, MQDC1-506RA)



MQDC1-506
2 m (6.5')
MQDC1-515
5 m (15')
MQDC1-530
9 m (30')



Banner Engineering Corp.

9714 10th Avenue North • Minneapolis, MN 55441 • 1-888-373-6767 • www.bannerengineering.com