


Flat Brackets

18 mm Bracket

SMBAMS18P

- Flat SMBAMS series bracket with 18 mm hole
- Articulation slots for 90°+ rotation
- 12-ga. (2.6 mm) cold-rolled steel
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

Hole center spacing: A = 26.0, A to B = 13.0
Hole size: A = 26.8 × 7.0, B = ø 6.5, C = ø 19.0




22 mm Bracket

SMBAMS22P

- Flat SMBAMS series bracket with 22 mm hole for mounting sensors
- Articulation slots for 90°+ rotation
- 12-ga. (2.6 mm) cold-rolled steel
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

Hole center spacing: A = 26.0, A to B = 13.0
Hole size: A = 26.8 × 7.0, B = ø 6.5, C = ø 22.5




30 mm Brackets

SMBAMS30P

- Flat SMBAMS series bracket
- 30 mm hole for mounting sensors
- Articulation slots for 90°+ rotation
- 12-gauge 300 series stainless steel
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)


Hole center spacing: A=26.0, A to B=13.0
Hole size: A=26.8 × 7.0, B=ø 6.5, C=ø 31.0



SMBAMS30PL52

- Flat SMBAMS series bracket with space for 70 × 40 mm label
- 30 mm hole for mounting sensors
- Articulation slots for 90°+ rotation
- 12-gauge (2.6 mm) cold-rolled steel
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

Hole center spacing: A=26.0, A to B=13.0
Hole size: A=26.8 × 7.0, B=ø 6.5, C=ø 31.0




SMBAMS30PL52R

- Flat SMBAMS series bracket with space for 60 × 58 mm label
- 30 mm hole for mounting sensors
- Articulation slots for 90°+ rotation
- 12-gauge (2.6 mm) cold-rolled steel
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

Hole center spacing: A=26.0, A to B=13.0
Hole size: A=26.8 × 7.0, B=ø 6.5, C=ø 31.0

SMBT30RTM


- Mount to a flat surface, such as a wall, with the sensor pointing up or down
- Mount on the top of a plastic tank to measure the level from outside the tank
- 12-gauge stainless steel
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)



LMBxx Lighting Brackets


ACC-WLC60-340-GSK-FDA-1

- Blue FDA-approved silicone gasket
- Thickness: 1.6 mm
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)



ACC-WLC60-340-GSK-N-1

- Black nitrile gasket
- Thickness: 1.5 mm
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)




Continued on page 2


Continued from page 1

LMBPTL110A45


- Angle mount
- For slotted extrusion and flat rail mounting
- 143 mm × 19 mm with a 30 mm depth
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**LMBPTL110F**


- Flat mount
- For slotted extrusion and flat rail mounting
- 150 mm × 25 mm
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**LMBSD50**


- Metal mounting bracket kit
- Hardware included
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**LMBWL32**


- Replaces the bracket that ships with the WLB32 light
- Stainless steel
- Includes 4 snap clips, 4 screws, and 2 insulator caps
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**LMBWL32U**


- Die-cast bracket for rugged applications
- Secured to light with included thumb screw
- Clearance hole for 6 mm (1/4 in) button head screw
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**LMBWL32UT**


- Die-cast bracket for rugged applications
- Secured to light with included thumb screw
- Integral 1/4-20 stud for mounting
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**LMBWL72F**


- Stainless steel
- Includes two surface mount brackets and four screws for mounting onto the housing
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**LMBWL92**


- Standard bracket that ships with the WLB92 light
- Stainless steel
- Includes two surface mount brackets, four screws, and four t-nuts
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**LMBWL92S**

- Surface mount brackets allow for mounting at the end of the light
- Stainless steel
- Includes two end brackets, four screws, and four t-nuts
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**LMBWLC60F**


- Set of two flat brackets
- 300 series stainless steel
- Includes M6 flathead screws for mounting to light
- Clearance for M6 or 1/4-20 mounting hardware
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)



MBK Brackets

EZA-MBK-9

- Two-bracket kit with 30 mm range of motion for mounting sensor
- 8-ga. cold-rolled steel with black corrosion-resistant zinc chromate finish
- M5 and M6 mounting hardware
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

Hole center spacing: Slot = 30.8**Hole size:** Slot = 21 × 7, Center hole = ø 32**LPA-MBK-180**

- Pair of inline (straight) brackets for two cascaded emitter/receiver pairs
- Fixed 180° orientation
- +10°/-30° sensor rotation
- 14-ga. (1.9 mm) steel, black zinc plated
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

Hole center spacing: A, B, C = 10.0, A to B = 73.3, A to C = 73.3**Hole size:** A, B, C = 15.5 × 5

Continued on page 3

Hole center spacing: A = 31.5, A to B = 15.8
Hole size: A, B = 15 × 7, C = ø 32


Technical drawing of a mechanical part with dimensions in mm and inches:

- Overall width: 154 mm [4.9"]
- Overall height: 46 mm [1.4"]
- Top left corner: 2 x R6 mm [0.2"]
- Top center hole: 21 mm [0.8"]
- Top right corner: 2 x R10 mm [0.4"]
- Bottom left corner: 2 x R3.5 mm [0.139"]
- Bottom center hole: 2 x 3.5 mm [0.139"]
- Bottom right corner: 2 x R10 mm [0.4"]
- Internal dimensions and features:
 - Top edge: 57 mm [2.2"]
 - Top edge: 10 mm [0.4"]
 - Top edge: 10 mm [0.4"]
 - Top edge: 4 mm [0.2"]
 - Top edge: 12 mm [0.8"]
 - Top edge: 18 mm [0.7"]
 - Top edge: 37 mm [1.5"]
 - Top edge: 1.6 mm [0.06"]
 - Internal hole: 10 mm [0.4"]
 - Internal hole: 30 mm [1.2"]
 - Internal hole: 2 x 3 mm [0.118"]
 - Internal hole: 15°


SMBAxx and SMBBxx Brackets

SMBABM


- 13-ga. zinc-plated low-carbon steel
- (4) M4 Phillips flathead screws included
- For mounting the light from the front
- Accommodates backlight models LED..B70X70..
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**SMBAMSLTFP**

- AMS mounting pattern
- 12 gauge stainless steel
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**SMBB25P**


- Zinc plated, Cold Rolled Steel
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)




SMBLxx Brackets

SMBLB

- Accommodates backlight models LED..B85X220..
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**SMBLG**

- L-GAGE sensor mounting bracket
- 304 Stainless Steel
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**SMBLH1**

- Main mounting bracket for LH Series sensor
- T-slot or "bolt-on" bracket for mounting one sensor
- Anodized Aluminum
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)


Hole size: A = M4




SMBPVLxx Brackets

SMBPVL2-225

- Flat bracket for mounting reflector inside bin
- 7 mm mounting hole
- 14 gauge cold rolled steel
- Includes retroreflective tape
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)

**SMBPVL2-500**


- Flat bracket for mounting reflector inside bin
- 7 mm mounting hole
- 14 gauge cold rolled steel
- Includes retroreflective tape
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)



SMBQxx and SMBxQxx Bracket

SMBAMSQ5XP


- Flat SMBAMS series bracket
- Articulation slots for 30 deg rotation
- 13-ga. 304 stainless steel
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)



SMBRxx Bracket

SMBR50


- R50 flat mount bracket
- M4 x 0.7 mm
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)



SMBVLxx Bracket

SMBVLA62X62S

- Inline bracket
- 14 gauge steel, black zinc-plated
- CAD Files: [DXF](#), [PDF](#), [IGS](#), [STP](#)



Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.