

Strip Light Comparison



KEY

- Cost Effective
- Slim Profile
- Multi Use
- Heavy Duty
- Multi Voltage

Model	Features	Specifications	White Lumens					Color Function		
			100	1000	2000	3000	4000	Single	Dimmable	Sealed (IP67)
WLS15	 	Power: 12 or 24 V DC Sizes: 6 (220–1200 mm) White Lm/ft: 350 lm/W @ 24 V: 73 Env. Rating: IP66, IP67	[Yellow bar from 100 to 1000]					Single Dual	✓	✓
WLS15H	 	Power: 24 V DC Sizes: 4 (360–1200 mm) White Lm/ft: 750 lm/W @ 24 V: 110 Env. Rating: IP66, IP67	[Yellow bar from 100 to 3000]					Single	✓	✓
WLS28-2		Power: 12 to 30 V DC Sizes: 8 (145–1130 mm) White Lm/ft: 800 lm/W @ 24 V: 110 Env. Rating: IP50 (unsealed) IP65, IP67, IP69K	[Yellow bar from 100 to 3000]					Single Dual Multi	✓	Option
WLS27		Power: 12 to 30 V DC Sizes: 8 (145–1130 mm) White Lm/ft: 800 lm/W @ 24 V: 110 Env. Rating: IP65, IP67, IP69K	[Yellow bar from 100 to 3000]					Single Dual Multi Pro	✓	✓
WLB32		Power: 12 to 30 V DC 90 to 264 V AC Sizes: 4 (285–1130 mm) White Lm/ft: 750 lm/W @ 24 V: 100 Env. Rating: IP50	[Yellow bar from 100 to 3000]					Single	–	–