

**Bright Light  
exactly where  
you need it**



**BANNER**<sup>®</sup>

more sensors, more solutions

[www.bannerengineering.com/eu](http://www.bannerengineering.com/eu)



Banner Engineering EMEA  
Park Lane, Culliganlaan 2F  
1831 Diegem | Belgium  
☎ +32 2 456 07 80

[www.bannerengineering.com/eu](http://www.bannerengineering.com/eu)  
[mail@bannerengineering.com](mailto:mail@bannerengineering.com)

# WL50-2 LED Work Light with Flex Arm

- Bright LED lighting technology, 185 Lumens, Cool White
- Low Supply Voltage: 12...30 VDC; 2 m cable
- Wide operating temperature range -40...+50° C
- Sealed to IP69K (IP67 for ON/OFF button model)
- Industrial grade flex arm design
- Vinyl coated for wet applications
- Mechanically adjustable for flexible spot light
- Direct machine mount or portable

## Examples

FLX18-FM30 for direct machine mount with WL50-2 work light

FLX18-12M30 with LMBE12RA mounting bracket and WL50-2 work light








FLX18-DM30 with SMBFLXMAGD magnetic mount and WL50-2PB work light with on/off button



WL50-2 cabled version



WL50-2PB with ON/OFF button, cabled version

Flex Arm type	Base Mount style	Installation type		Cable routing		Mounting Bracket Options		
		Fixed	Portable (with bracket)	Through base	External	Magnetic	Clamp	Fixed
FLX18-12M30	 1/2-14 NPSM	✓	✓	✓	✗	 SMBFLXMAG	✗	 LMBE12RA
FLX18-DM30	 2 x 1/4-20W	✓	✓	✗	✓	 SMBFLXMAGD	 SMBFLXCLAMPD	✗
FLX18-FM30	 3-Hole Flange	✓	✗	✓	✗	Direct mount only		



Banner offers a full range of sensing solutions  
[www.bannerengineering.com/eu](http://www.bannerengineering.com/eu)

