

Features

DC-Operated Indicators with Steady or Pulsed Sound Indication

To view or download the latest technical information about this product, including specifications, dimensions, accessories, and wiring, go to www.bannerengineering.com.

		• Rugged, cost-effective, and easy-to-install indicators available in K50 or K80 housing style • Steady or pulsed sound indication • Illuminated dome provides a big, easy-to-see green, red, or yellow job light • Compact devices are completely self-contained, no controller needed • Choose NPN or PNP input depending on model • Immune to EMI and RFI interference • 12 V DC to 30 V DC operation • Three color LED function: green, red, and yellow
---	---	---



WARNING:

- Do not use this device for personnel protection
- Using this device for personnel protection could result in serious injury or death.
- This device does not include the self-checking redundant circuitry necessary to allow its use in personnel safety applications. A device failure or malfunction can cause either an energized (on) or de-energized (off) output condition.

Models

Model ⁽¹⁾	Construction	Audible Tone ⁽²⁾	Input
K50LGRA1YQP	50 mm dome/30 mm mount polycarbonate	Steady (75 dB)	ON/O
K50LGRA1YQ			N/O/N
K50LGRA2YQP		Pulsed (75 dB)	ON/O
K50LGRA2YQ			N/O/N
K50LGRA1LYQP		Low Steady (95 dB)	ON/O
K50LGRA1LYQ			N/O/N
K80LGRA1YQP	50 mm dome/flat or DIN-mount polycarbonate, nylon	Steady (75 dB)	ON/O
K80LGRA1YQ			N/O/N
K80LGRA2YQP		Pulsed (75 dB)	ON/O
K80LGRA2YQ			N/O/N
K80LGRA1LYQP		Low Steady (95 dB)	ON/O
K80LGRA1LYQ			N/O/N

Wiring Diagrams

		Key: - L = Brown 2 = White 3 = Blue 4 = Black - S = Gray - G = Green light - R = Red light - Y = Yellow light - A = Alarm
---	---	--

⁽¹⁾ Integral quick disconnect models are listed.

- To order the 150 mm (6 in) PVC cable model, replace the suffix "Q" with "QP" in the model number. For example, K90LGRA1YQP.
- K90L Models: To order the 2 m (6.5 ft) PVC cable model, omit the suffix "Q" in the model number. For example, K90LGRA1YP.
- K90L Models: To order the terminal wired model, omit the suffix "Q" in the model number. For example, K90LGRA2YP.
- Models with a quick disconnect require a mating cordset.
- Contact Banner Engineering for other colors and color combinations.

⁽²⁾ Typical decibel level is at a distance of 1 m.

Specifications

- Supply Voltage and Current
18 V DC to 30 V DC at 40 mA maximum, per LED color (alarm)
- Input Response Time
Indicator ON/OFF: 10 ms maximum
- Oscillation Frequency
A1 models: 3 kHz $\pm$ 500 Hz
A2 models: 3 kHz $\pm$ 500 Hz; pulse rate 3 Hz $\pm$ 20%
A/L1 models: 2.7 kHz $\pm$ 500 Hz
- Operating Conditions
-20 °C to +50 °C (-4 °F to +122 °F)
- Environmental Rating
IP 50
K50L models only: NEMA/UL Type 4X, 13
- Indicators
LEDs or audible independently selected: green, red, yellow

- Certifications
- CE** Banner Engineering BV
Park Lane, Culliganlaan 2F bus 3
1831 Diegem, BELGIUM
- UKCA** Turner Banner LTD Blenheim House
Blenheim Court
Wickford, Essex SS17 8YU
GREAT BRITAIN
(K50L models only)
- UL LISTED**
(K50L models only)
- Connections
Integral 5-pin M12 male quick-disconnect connector, $\varnothing$ 150 mm (6 in) PVC-jacketed cable with a 5-pin M12 male quick-disconnect connector, $\varnothing$ 2 m (6.5 ft) unterminated 5-wire PVC-jacketed cable, depending on model
K80L Models: Terminal-wired models for use with bulk cable available

Required Overcurrent Protection


WARNING: Electrical connections must be made by qualified personnel in accordance with local and national electrical codes and regulations.

Overcurrent protection is required to be provided by end product application per the supplied cable. Overcurrent protection may be provided with external fusing or via Current Limiting, Class 2 Power Supply.
Supply wiring leads < 24 AWG shall not be spliced. For additional product support, go to www.bannerengineering.com.

Supply Wiring (AWG)	Required Overcurrent Protection (A)	Supply Wiring (AWG)	Required Overcurrent Protection (A)
20	5.0	26	1.0
22	3.0	28	0.8
24	1.0	30	0.5




Dimensions

All measurements are listed in millimeters [inches], unless noted otherwise.




Accessories

Cordsets

5 Pin Threaded M12 Connectors – Single Ended				
Model	Length	Style	Dimensions	Pinout (Female)
MQDC1-501.5	0.5 m (1.5 m)	Straight		 1 = Brown 2 = White 3 = Blue 4 = Black 5 = Gray
MQDC1-503	0.9 m (2.9 m)			
MQDC1-506	1 m (6.5 m)			
MQDC1-515	5 m (16.4 m)			
MQDC1-530	9 m (29.5 m)			
MQDC1-560	18 m (59 m)			
MQDC1-5100	31 m (101.7 m)			
MQDC1-506RA	1 m (6.5 m)	Right Angle		
MQDC1-515RA	5 m (16.4 m)			
MQDC1-530RA	9 m (29.5 m)			
MQDC1-560RA	18 m (62.3 m)			

Brackets

K80L Bracket

SMBDX80DIN • Black reinforced thermoplastic • Bracket for mounting on a 35 mm DIN rail	
--	---


K50L Brackets

SMB30A

- Right-angle bracket with curved slot for versatile orientation
- Clearance for M6 (¼ in) hardware
- Mounting hole for 30 mm sensor
- 12-gauge stainless steel

Hole center spacing: A to B=40

Hole size: A=ø 6.3, B= 27.1 × 6.3, C=ø 30.5




SMB30MM

- 12-gauge stainless steel bracket with curved mounting slots for versatile orientation
- Clearance for M6 (¼ in) hardware
- Mounting hole for 30 mm sensor

Hole center spacing: A to B = 51, A to C = 25.4

Hole size: A = 42.6 × 7, B = ø 6.4, C = ø 30.1




SMBAMS30RA

- Right-angle SMBAMS series bracket
- 30 mm hole for mounting sensors
- Articulation slots for 90°+ rotation
- 12-gauge (2.6 mm) cold-rolled steel

Hole center spacing: A=26.0, A to B=13.0

Hole size: A=26.8 × 7.0, B=ø 6.5, C=ø 31.0




SMB30SC

- Swivel bracket with 30 mm mounting hole for sensor
- Black reinforced thermoplastic polyester
- Stainless steel mounting and swivel locking hardware included

Hole center spacing: A=ø 50.8

Hole size: A=ø 7.0, B=ø 30.0




SMB30FA

- Swivel bracket with tilt and pan movement for precise adjustment
- Mounting hole for 30 mm sensor
- 12-gauge 304 stainless steel
- Easy sensor mounting to extrude rail T-slot
- Metric- and inch-size bolt available

Bolt thread: SMB30FA, A= 3/8 16 × 2 in; SMB30FAM10, A= M10 1.5 × 50

Hole size: B= ø 30.1




SMBAMS30P

- Flat SMBAMS series bracket
- 30 mm hole for mounting sensors
- Articulation slots for 90°+ rotation
- 12-gauge 300 series stainless steel

Hole center spacing: A=26.0, A to B=13.0

Hole size: A=26.8 × 7.0, B=ø 6.5, C=ø 31.0



SMB30FVK

- V-clamp, flat bracket and fasteners for mounting to pipe or extensions
- Clamp accommodates 28 mm dia. tubing or 1 in. square extrusions
- 30 mm hole for mounting sensors


Hole size: A= ø 31



SMB30RAVK


- V-clamp, right-angle bracket and fasteners for mounting sensors to pipe or extrusion
- Clamp accommodates 28 mm dia. tubing or 1 in. square extrusions
- 30 mm hole for mounting sensors

Hole size: A = $\varnothing$ 30.5

**LMBE12RA35**


- Direct mounting of stand off pipe, with common bracket type
- Zinc plated steel
- 1/2 - 14 NPSM nut
- Mounting distance from the wall to the center of the 1/2 - 14 NPSM nut is 35 mm

Hole center spacing: 20.0

**LMBE12RA45**

- Direct mounting of stand off pipe, with common bracket type
- Zinc plated steel
- 1/2 - 14 NPSM nut
- Mounting distance from the wall to the center of the 1/2 - 14 NPSM nut is 45 mm

Hole center spacing: 35.0



Banner Engineering Corp Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.

Document title: EZ-LIGHT® K50L and K80L Audible Indicator Lights

Part number: 135242

Revision: G

Original Instructions

© Banner Engineering Corp. All rights reserved.



135242