



Rev: N



EC / UKCA Declaration of Conformity



Attached Schedule — Schedule 1 of 1

Product(s) Covered Under this Declaration:

(Excluding K30 hazardous area ATEX models)

K30L Dome Indicator

Models K30L; may be followed by 2; may be followed by up to three letters to signify colour; may be followed by 7, 8 or 9; may be followed by P or N; may be followed by Q, QS, QP, QPMA, QTASK, T or W/xx signifying cable length*

K30 Pro Dome Indicators

Models K30P; followed by L; may be followed by L; may be followed by P; followed by S or K; followed by Q, QP, QPxx (xx is length), Q2PS, Q2PSxx, Q2PMA, Q2PMAxx or W/xx (xx is length of cable). *

*All models above may include a prefix and/or suffix that includes up to 7 alphanumeric characters not impacting hardware or emission profile, or product safety approval.

Directive(s) / Regulation(s) and Standard(s) - Notified / Approval Body

EU EMC Directive 2014/53/EU
UK EMC Regulations 2016
BS EN 60947-1:2007
BS EN 60947-1:2007 A1:2011
BS EN 60947-1:2007 A2:2014

EU RoHS Directive 2011/65/EU as amended by 2015/863/EU
UK RoHS Regulations 2012
BS EN IEC 63000:2018
BS EN 50581:2012

Directive(s) / Regulation(s) and Standard(s) - Notified / Approval Body